

Check Valves




Service Parts Information

Pilot Operated Check Valve

4CT-06-(D)-*20


4CG-06-(D)-*20

Model	Spring	P.S.I.	Check Valve	Guide Poppet
4CT-03-A-20	352439	30	359861	359838
4CT-03-DA-20			342225	352440
4CT-03-C-20	388350	75	359861	359858
4CT-03-DC-20			342225	352440
4CT-03-F-20	388351	150	359861	388357
4CT-03-DF20			342225	388356



Model Code

4C * - 03 - (D) * - 20



1 Model Series

4C - Pilot operated check valve

4 Decompression Feature

Omitted - No decompression feature

8 Design

2 Mounting

G - Gasket mounted
T - Threaded connections

5 Pressure Range

A - 30 psi
C - 75 psi
F - 150 psi


3 30 Series

4CG-03-(D)*-20

Model	Spring	P.S.I.	Check Valve	Guide Poppet
4CG-03-A-20	352439	30	359861	359858
4CG-03-DA-20			342225	352440
4CG-03-C-20	388350	75	359861	359858
4CG-03-DC-20			342225	352440
4CG-03-F-20	388351	150	359861	388357
4CG-03-DF-20			342225	388356

Pressure Range

A - 30 psi
C - 75 psi
F - 150 psi



For satisfactory service life of these components, use full flow filtration to provide fluid which meets ISO cleanliness code 20/18/15 or cleaner. Selections from Eaton OFF, OFR and OFRS filter series are recommended.

Printed in U.S.A.