# EAT-N Aeroquip

## **Easy Couple**

**Innovation Sheet** 





### Strong Brand Name Recognition

One of the best hose products in the Boston lineup is now available to Aeroquip distributors. Just like its name, Boston<sup>®</sup> Easy Couple is easy to sell and has strong brand name recognition in the air and tool markets.

Easy Couple, part number H201, is qualified with the standard Aeroquip Socketless<sup>™</sup> fitting program.

Compatible with fuel, lubricating oils, air and water, Easy Couple services a variety of applications from machine tools to lubricating oil lines.

#### **Features**

- Lightweight and flexible
- Vinyl Nitrile RMA Class A tube for optimal oil resistance
- Braided reinforcement
- Available with neoprene MSHA approved black cover

#### Benefits

- Braided construction provides better coupling retention for impulse applications
- Qualified with push on fittings eliminates the need for clamps
- Abrasion, oil and weather resistant
- Easy identification
- Easy to handle



H201 Boston Easy Couple General Purpose Hose



#### SPECIFICATIONS

PART NUMBER	MAXIMUM HOSE I.D.	MAXIMUM HOSE O.D.	MINIMUM OPERATING PRESSURE	MINIMUM BURST PRESSURE	BEND RADIUS	WEIGHT PER FOOT	LENGTH OFFERED
	mm in fr	mm in fr	bar psi	bar psi	mm in	kg/m lbs/ft	feet
(#)	$\bigcirc$	$\bigcirc$	$\bigcirc$	$\bigcirc$	Ø		
H20104BK-250R H20104BK-500R	6,4 0.25 1/4	12,7 0.50 1/2	17,2 250	69,0 1,000	76,2 3.00	4,1 9	250 500
H20106BK-250R H20106BK-500R	9,5 0.38 3/8	16,7 0.65 21/32	17,2 250	69,0 1,000	76,2 3.00	5,9 13	250 500
H20108BK-250R H20108BK-500R	12,7 0.50 1/2	19,1 0.75 3/4	17,2 250	69,0 1,000	127,0 5.00	6,8 15	250 500
H20110BK-250R	15,9 0.63 5/8	23,8 0.93 15/16	17,2 250	69,0 1,000	152,4 6.00	10,4 23	250
H20112BK-250R	19,1 0.75 3/4	26,2 1.03 1-1/32	17,2 250	69,0 1,000	177,8 7.00	11,8 26	250

Inner Tube: Nitrile

Reinforcement: 1 Fiber Braid

Cover: Neoprene (Black), Vinyl Nitrile (Colored Hoses)

Temp. Range: -40°F to +200°F (-40°C to +100°C)

**Typical Application:** General purpose truck hose. High temperature hydraulic, air brake and diesel fuel applications. MSHA Accepted (Black only)

\* Hose available in black (BK) and blue (BU), example H20104(BU)

Fitting: Hose is approved with Aeroquip Socketless™ fittings only.

WARNING: It is important to use the correct fitting with any hose product to ensure a proper connection. Only use the fittings suggested by Eaton for this hose product. Mixing fittings and hoses by different manufacturers can lead to an unstable connection, due to differences in manufacturing techniques and tolerances. Such connections can fail and have the potential to spray and cause personal injury or property damage.

Eaton 14615 Lone Oak Road Eden Prairie, MN 55344 USA Tel: 952 937-9800 Fax: 952 974-7722 www.hydraulics.eaton.com Eaton 20 Rosamond Road Footscray Victoria 3011 Australia Tel: (61) 3 9319 8222 Fax: (61) 3 9318 5714 Eaton Dr.-Reckeweg-Str. 1 D-76532 Baden-Baden Germany Tel: (49) 7221 682-0 Fax: (49) 7221 682-788



© 2006 Eaton Corporation All Rights Reserved Printed in USA Document No. A-HOBR-MS003-E July 2006