# F-T-N Aeroquip

### Aeroquip Nickel-Plated Aluminum Fittings and Adapters



Aeroquip's complete line of electroless nickel-plated fittings and adapters provide a lightweight, low-cost alternative to higher priced, heavy stainless steel components.

The Aeroquip nickel-plated fittings and adapters are ideal for applications requiring superior corrosion resistance and a neutral in color – yet high-tech and classy – appearance.

#### Applications

- Hot rods/street rods
- Show vehicles
- Water craft
- Racing vehicles
- Motorcycles

#### **Features**

- Utilize the latest in electroless plating technology
- Lightweight aluminum construction which has the appearance of higher priced, heavy stainless steel
- Appearance that is ideal for street rod, marine, cycle and show car applications

#### **Benefits**

- Consistent appearance
- Corrosion resistance
- Lightweight













#### **Technical Data**

#### NICKEL-PLATED ALUMINUM FITTINGS & ADAPTERS

PART NUMBER	REUSABLE FITTINGS	DASH SIZE
FCE1012	Straight – Swivel	-06
FCE1013	Straight – Swivel	-08
FCE1014	Straight – Swivel	-10
FCE1015	Straight – Swivel	-12
FCE4022	45° Elbow – Swivel	-06
FCE4023	45° Elbow – Swivel	-08
FCE4024	45° Elbow – Swivel	-10
FCE4025	45° Elbow – Swivel	-12
FCE4032	90° Elbow – Swivel	-06
FCE4033	90° Elbow – Swivel	-08
FCE4034	90° Elbow – Swivel	-10
FCE4035	90° Elbow – Swivel	-12

PART	SOCKETLES	S™ FITTINGS	DASH SIZE
FCE1512	Straight -	06	
FCE1513	Straight	-08	
FCE1514	Straight	-10	
FCE1515	Straight	-12	
FCE1522	45° Elbow	-06	
FCE1523	45° Elbow	-08	
FCE1524	45° Elbow	-10	
FCE1525	45° Elbow	-12	
FCE1532	90° Elbow	-06	
FCE1533	90° Elbow	-08	
FCE1534	90° Elbow	-10	
FCE1535	90° Elbow	-12	

ADAPTERS	DASH & THREAD SIZE
Straight – Male Connector – AN Flare to Pipe	-06 to ¼″
Straight – Male Connector – AN Flare to Pipe	-06 to ¼"
Straight – Male Connector – AN Flare to Pipe	-06 to ¾″
Straight – Male Connector – AN Flare to Pipe	-08 to ¾″
Straight – Male Connector – AN Flare to Pipe	-08 to ½"
Straight – Male Connector – AN Flare to Pipe	-10 to ½"
Straight – Male Connector – AN Flare to Pipe	-12 to ½"
Straight – Male Connector – AN Flare to Pipe	-12 to ¾"
Straight – Male Connector – AN Flare to Pipe	-12 to 1"
Straight – Fuel Pump – Male Pipe for Holley Electric Fuel Pumps	-10 to ¾″
45° Male Elbow – AN Flare to Pipe	-06 to ¼"
45° Male Elbow – AN Flare to Pipe	-08 to ¾″
45° Male Elbow – AN Flare to Pipe	-10 to ½"
45° Male Elbow – AN Flare to Pipe	-12 to ¾"
90° Male Elbow – AN Flare to Pipe	-06 to ¼″
90° Male Elbow – AN Flare to Pipe	-06 to ¼"
90° Male Elbow – AN Flare to Pipe	-06 to ¾"
90° Male Elbow – AN Flare to Pipe	-08 to ¾"
90° Male Elbow – AN Flare to Pipe	-08 to ½"
90° Male Elbow – AN Flare to Pipe	-10 to ½"
90° Male Elbow – AN Flare to Pipe	-12 to ½"
90° Male Elbow –	-12 to ¾"
	Straight – Male Connector – AN Flare to Pipe Straight – Straight – Male Connector – AN Flare to Pipe Straight – Fuel Pump – Male Pipe for Holley Electric Fuel Pumps 45° Male Elbow – AN Flare to Pipe 45° Male Elbow – AN Flare to Pipe 90° Male Elbow – AN Flare to Pipe

Eaton 14615 Lone Oak Road Eden Prairie, MN 55344 USA Tel: 952 937-9800 Fax: 952 974-7722 www.hydraulics.eaton.com

#### Eaton 20 Rosamond Road Footscray Victoria 3011 Australia Tel: (61) 3 9319 8222 Fax: (61) 3 9318 5714

#### Eaton 46 New Lane, Havant Hampshire PO9 2NB England

Tel: (44) 23 92 486 451 Fax: (44) 23 92 487 110

> © 2002 Eaton Corporation All Rights Reserved Printed in USA Document No. A-SPPE-MS001-E Supercedes Form No. JC212B August 2002

## **FA**eroquip